

Reference - Rotary Cutters - Please 3-hole punch



ROTARY CUTTERS

RC SERIES SELECTION GUIDE

Width	Duty	equipment Description	PTO HP Capacity	Quick Hitch Compatible	Driveline/ Protection	Front Deflector	Rear Deflector	Tail Wheel/ Tires (Qty)	Level Lift	Deck Thickness	Max. Cut Capacity
SINGLE SPINDLE (3-POINT HITCH)											
4 ft.	Standard Duty	RC480 4 ft. Standard Duty	up to 48	Yes	Cat. 4 w/ Shear Pin ¹	None ²	Rubber ²	Single Laminated	N/A	10 Ga. (.1345")	2'
5 ft.	Standard Duty	RC600 5 ft. Standard Duty	up to 48	Yes	Cat. 4 w/ Shear Pin ¹	None ²	Rubber ²	Single Laminated	N/A	7 Ga. (.1793")	2'
	Medium Duty	RC605 5 ft. Medium Duty	up to 65	Yes	Cat. 4 w/ Slip Clutch	None ²	Rubber ²	Single Laminated ³	N/A	7 Ga. (.1793")	2-1/2'
6 ft.	Standard Duty	RC720 6 ft. Standard Duty	up to 48	Yes	Cat. 4 w/ Shear Pin ¹	None ²	Rubber ²	Single Laminated	N/A	7 Ga. (.1793")	2'
	Medium Duty	RC725 6 ft. Medium Duty	up to 65	Yes	Cat. 4 w/ Slip Clutch	None ²	Rubber ²	Single Laminated ³	N/A	7 Ga. (.1793")	2-1/2'
	Heavy Duty	RC727 6 ft. Heavy Duty	up to 95	Yes	Cat. 5 w/ Slip Clutch	Chain	Chain	Single Laminated ³	N/A	7 Ga. (.1793")	3'
7 ft.	Medium Duty	RC840 7 ft. Medium Duty	up to 65	Yes	Cat. 4 w/ Slip Clutch	None ²	Rubber ²	Single Laminated ³	N/A	7 Ga. (.1793")	2-1/2'
	Heavy Duty	RC845 7 ft. Heavy Duty	up to 95	Yes	Cat. 5 w/ Slip Clutch	Chain	Chain	Single Laminated ³	N/A	7 Ga. (.1793")	3'
MULTIPLE SPINDLE (PULL TYPE)											
12 ft.	Medium Duty	RC1440 12 ft. Medium Duty 540RPM	40-70	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Laminated (4)	Mechanical	7 Ga. (.1793")	3'
	Heavy Duty	RC1440 12 ft. Heavy Duty 540RPM	40-100	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Aircraft (4)	Mechanical	7 Ga. (.1793")	3'
15 ft.	Heavy Duty	RC1800 15 ft. Heavy Duty 540RPM	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Laminated (6)	Mechanical	7 Ga. (.1793")	3-1/2'
	Heavy Duty	RC1800 15 ft. Heavy Duty 1000RPM 1-3/8	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Aircraft (6)	Hydraulic	7 Ga. (.1793")	3-1/2'
	Heavy Duty	RC1800 15 ft. Heavy Duty 1000RPM 1-3/4	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Aircraft (6)	Hydraulic	7 Ga. (.1793")	3-1/2'
	Heavy Duty (Smooth Deck)	RC1800 15 ft. H.D. Smooth Deck 540RPM DD	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Laminated (6)	Mechanical	7 Ga. (.1793")	3-1/2'
	Heavy Duty (Smooth Deck)	RC1800 15 ft. H.D. Smooth Deck 1000 1-3/8 DD	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Aircraft (6)	Hydraulic	7 Ga. (.1793")	3-1/2'
	Heavy Duty (Smooth Deck)	RC1800 15 ft. H.D. Smooth Deck 1000 1-3/4 DD	up to 210	N/A	Main - Cat. 5 CV w/Slip Clutch; Wings - Cat. 4 w/ Slip Clutch	Chain	Chain	Aircraft (6)	Hydraulic	7 Ga. (.1793")	3-1/2'

¹Slip Clutch Optional ²Chain Optional ³Dual Optional

SAFETY NEVER HURTS!™ Always read the Operators Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2021 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates.

Printed in U.S.A. www.caseih.com

CIH21062901 08/2021